Be Safe.. Think

B-Safe

PROFESSIONAL ROOFERS KIT

BK061015PR0

140KG RATED

CONTENTS

- BH01120 Fall Arrest Harness
- BS010115A Rope Safety Line -15m Kernmantle Rope fitted with double action self-locking hook at one end and manual rope adjuster
- **BP03102** 2m attachment strap 25mm web rated for 1 Person
- BL01112PR0-ADJ 2m adjustable webbing shock absorbing lanyard with Snap Hooks 50-140kg rated
- BSK0003-16 Alloy Steel Twist Lock Karabiner
- BA00024 Suspension Trauma Straps
- B-SAFE Back Pack











MADE IN CHINA


Manufactured for Beaver Brands 55 Sarah Andrews Close

55 Sarah Andrews Close Erskine Park NSW 2759 Locked Bag 5001, St Clair NSW 2759 National Sales: 1300 783 606 beaverbrands.com.au




bsafe.com.au


B-Safe ROOFERS KIT 6 STEP GUIDE




Set ladder and establish Anchor then Connect Rope Line (use attachment strap or T Bar Anchor)



Test connection, move adjuster to knot end and throw to opposite side (use of throw line and sandbag is recommended)




Relocate ladder, pull rope tight, don harness, connect shock absorber/lanyard to adjuster and squat to test taughtness of ropeline



Climb ladder moving adjuster as you climb to minimise free fall before the shock absorber would be deployed



Take care when transferring to roof Establish Restraint Technique position



Once Restraint Technique position is established work within a 60° arc, avoiding pendulum swing falls

NOTE: THERE IS NO SUBSTITUTE FOR COMPETENCY BASE TRAINING