

# LIFESTYLE SAFETY RANGE



## VISION

Lightweight athletic safety shoe designed specifically for light industry including warehousing, transport and garbage collectors who clock up big miles on their feet with minimal wear and tear on their footwear. The heat welded exoSHIELD upper ensures a seam free upper for maximum comfort and durability.



**SIZES**  
**4-13**  
**WEIGHT**  
**489<sup>g</sup>**

### COLOURS



### BLACK/RED SIZES

**6-13**



## PERFORMANCE SYSTEMS

### SYST-M<sup>®</sup>

Design philosophy that integrates series of technologies and design features to provide movement specific support and flexibility.

### articulatedFIT<sup>™</sup>

Upper design system to allow the natural movement of the foot and ankle from heel strike to toe-off.

### WIDEcap

Wide anatomical shaped toecap to reduce rubbing and nerve impingement.



## SAFETY SYSTEMS

### COMPOSITEToecap

Lightweight, metal free, nonconductive, insulating and airport friendly safety toecap that complies with Australian/New Zealand (AS/NZ S2210), European (EN-ISO 20345) and American standards (ASTM F2413-11).

### slipRESIST-C

Sole slip resistant to soap (SLS) on ceramic tiles and glyceryl on steel plate.

### ANTI-STATIC

Minimises static electricity build up for safety in volatile environments.

### fueloilRESIST

Sole resists breakdown to fuel oil.

### LOWcatchsole

Low profile sole at the toe to reduce the risk of tripping.

### ScuffCAP

Improves durability in high wear zones.

### exoSHIELD

External TPU welded overlay to be seam free and provide support and durability.

# HAZARD SOLUTION GUIDE

## TRIPS & FALLS

- Lightweight footwear to reduce fatigue of the leg muscles that lift the toes.
- **LOWcatchsole** to improve swing phase ground clearance at the toe to reduce the risk of tripping.

## COMBUSTIBLE MATERIALS

- **ANTI-STATIC** certified footwear minimises static electricity build-up for safety in volatile environments.
- Metal-free footwear can reduce the risk of spark ignition.

## PRODUCT DETAILS

### APPROVED STANDARDS

- AS/NZS 2210.3 (Class I S1 SRC)
- EN - ISO 20345 (Class I S1 SRC)
- ASTM F2413-11 (M/I/75/C/75/SD)

**OUTSOLE:** Rubber

**TOECAP:** Composite

**UPPER:** Synthetic Mesh

**PRODUCT CODES:**

xxx represents sizing i.e. size 12 is 120 and size 9.5 is 095

**NAVY/ORANGE CODE:**

MKVISION-NOFxxx

**BLACK/RED CODE:**

MKVISION-BDFxxx



## FIT GRID

	HIGH ARCH		
		VISION	
NARROW			WIDE
	LOW ARCH		

## SOLE SELECTION GRID

	SLIPPERY/WET		
		VISION	
SMOOTH			UNEVEN
	MUDDY/CONTAMINATED		

## MACKBOOTS.COM.AU | 1300 350 216

Mack Footwear is sold under licence from Mack Trucks, Inc. All rights reserved. \*Weight disclaimer. Footwear weights are based on a men's UK8 for a single shoe or boot and a ladies UK10 for women's shoes. Due to the nature of manufacturing there will be subtle variation between pairs. Disclaimer: Every reasonable effort has been made to ensure the accuracy of the Product information in this document. This document must not be regarded as an infallible guide. **Mack Boots™** accepts no responsibility in this regard. As product details may change from time to time please contact **Mack Boots™** to gain the latest information.



AS/NZS 2210 Australian /New Zealand Standards  
 EN - ISO 20345 European Standards  
 ASTM F2413 American Standards