LADIES RANGE





PERFORMANCE SYSTEMS

0/	<u> </u>	Т	v.	(R)
-	7 - 7		11	_

Design philosophy that integrates series of technologies and design features to provide movement specific support and flexibility.

M-WRAP™

Medial wrapped midsole design provides rearfoot stability for those that need it. Particularly important for people with flat feet and those that wear orthotics or arch supports.

Hydrodynamic[™]

Sole shape and tread pattern engineered to optimise fluid dispersion beneath the foot to minimise slips.

asym*BEVEL*™

Heel shaped to match the natural heel strike position during walking to maximise contact area and provide a smooth ride.

Ortholite[®]

Breathable memory foam insole that moulds to the foot providing a customised fit and helping to reduce in-shoe friction.

decouple GROOVE™

Flex groove along the length of the sole to provide flexibility to allow a smooth transition from initial contact to foot flat and improve terrain adaption.

<u>soft</u>board™

Constructed on cushioned foam insole board for a smooth ride.

radiator**TECH**™

Manufacturing technique used to improve the breathability of leather and lining materials.

endurelon™

Specifically compounded phylon midsole to improve cushioning rebound characteristics and durability.

cuboidNOTCH™

Sole design feature to provide support on the outside of the foot, particularly when used with foot orthotics.

FITCHECK

Registered fitting guide printed on the insole to indicate the correct spacing between the end of the longest toe and the toecap.

SAFETY SYSTEMS

STEELToecap

Lightweight, metal free, nonconductive, insulating and airport friendly safety toecap that complies with Australian/New Zealand (AS/NZ S2210), European (EN-ISO 20345) & American standards (ASTM F2413-11).

slipRESIST-C

Sole slip resistant to soap (SLS) on ceramic tiles and glyceryl on steel plate.

300°cHeatResistant

Nitrile rubber sole that is hard wearing and resistant to extreme heat.

fueloil RESIST

Sole resists breakdown to fuel oil.

ANTI-STATIC

Minimises static electricity build up for safety in volatile environments.

H₂ORESISTANT

Footwear designed to shed water.

Ladder**Heel**

Sole design minimises slip risk on ladders.

LOWcatchsole

Low profile sole at the toe to reduce the risk of tripping.

HAZARD SOLUTION GUIDE

SLIPS

- asymBEVEL™ to match the natural heel strike position during walking to maximise ground contact area during initial contact.
- Hydrodynamic[™] sole shape and tread pattern engineered to optimise fluid dispersion beneath the foot to minimise slips.

TRIPS & FALLS


- Lightweight footwear to reduce fatigue of the leg muscles that lift the toes.
- LOWcatchsole to improve swing phase ground clearance at the toe to reduce the risk of tripping.
- asymBEVEL™ to match the natural heel strike position during walking to minimise fatigue of the leg muscles that lift the toes.

COMBUSTIBLE MATERIALS


 ANTI-STATIC certified footwear minimises static electricity build-up for safety in volatile environments.

HOT CONTACT


 300°cHeatResistant nitrile rubber outsole provides protection in high heat environments. Ideal for workers in road construction and other occupations that expose workers to hot surfaces or objects.



FIT GRID



SOLE SELECTION GRID



MACKBOOTS.COM.AU | 1300 350 216

Mack Footwear is sold under licence from Mack Trucks, Inc. All rights reserved. "Weight disclaimer. Footwear weights are based on a men's UK8 for a single shoe or boot and a ladies UK10 for women's shoes. Due to the nature of manufacturing there will be subtle variation between pairs. Disclaimer: Every reasonable effort has been made to ensure the accuracy of the Product information in this document. This document must not be regarded as an infallible guide. **Mack Boots™** accepts no responsibility in this regard. As product details may change from time to time please contact **Mack Boots™** to gain the latest information.



AS/NZS 2210 Australian /New Zealand Standards EN - ISO 20345 European Standards ASTM F2413 American Standards